

US009410935B2

# (12) United States Patent

Aquino Olivos et al.

(54) MEASUREMENT PROCESS OF MINIMUM MISCIBILITY PRESSURE (MMP) AND CRITICAL POINTS OF A GAS IN CRUDE OILS OR BINARY MIXTURES

(71) Applicant: **INSTITUTO MEXICANO DEL PETROLEO**, Mexico City (MX)

(72) Inventors: Marco Antonio Aquino Olivos, Mexico City (MX); Adriana de Jesus Aguirre Gutierrez. Mexico City (MX): Jose

Luis Mendoza de la Cruz, Mexico City (MX); Sergio Alvarez Badillo, Mexico

City (MX)

(73) Assignee: **INSTITUTO MEXICANO DEL PETROLEO**, Mexico City (MX)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 14/711,385

(22) Filed: **May 13, 2015** 

(65) **Prior Publication Data** 

US 2015/0330962 A1 Nov. 19, 2015

(30) Foreign Application Priority Data

May 14, 2014 (MX) ...... MX/a/2014/005812

(51) **Int. Cl.** *E21B 47/06* 

G01N 33/28

(2012.01) (2006.01)

(Continued)

(52) U.S. Cl.

(58) Field of Classification Search

CPC ... G01N 33/2823; G01N 33/28; G01N 25/00; G01N 33/26; G01N 25/02; G01N 25/4873;

(10) Patent No.: US 9

US 9,410,935 B2

(45) **Date of Patent:** 

Aug. 9, 2016

E21B 47/06; E21B 43/25; E21B 49/08; G01L 7/18; G01L 9/00; Y10T 436/214 See application file for complete search history.

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

4,455,860 A 6/1984 Cullick et al. 4,621,522 A 11/1986 Christiansen et al.

(Continued)

# FOREIGN PATENT DOCUMENTS

FR 1253235 1/1961 GB 858270 1/1961

# OTHER PUBLICATIONS

Alvarez-Badillo, S. et al., 14th International Conference on Petroleum Phase Behavior and Fouling, Jun. 10-13, 2013, Rueil Malmaison, France, Oral Jun. 12, 2013, "OF2—C02 Minimum Pressure by Scanning Transitiometry".\*

(Continued)

Primary Examiner — Jennifer Wecker

(74) Attorney, Agent, or Firm — Dickinson Wright PLLC

(57) ABSTRACT

The present invention provides a new process of the transitiometric scanning technique to determine in an experimental way the minimum miscibility pressure of any sample of hydrocarbon at constant temperature (from the atmospheric temperature to 673 K) in the pressure interval of the atmospheric temperature to 400 MPa, including pressure at which the organic matter will precipitate due to the CO<sub>2</sub> injection, based on a transitometric technique which has proved to be reliable, highly accurate and highly reproducible. The apparatus used is based on a highly accurate control of the pVT variables and the calorimetric determination of the present phase transitions during the injection process of gases into hydrocarbons. Accurate control of pVT variables enables the determination of the derivative thermodynamic variables useful to define the type of phase transition.

### 4 Claims, 6 Drawing Sheets

